GL/PD-06-03

5.5 Finished Dimensions. The finished Jacket shall conform to the measurements listed in the Table VIII.

TABLE VIII. Finished Dimensions (Measurements in Inches)

				¥	V			
REGULAR		XS	s '	. M.≴	Life	XL	2XL	TOL +/-
1	ACROSS CHEST 1/	22	24		54 ₂₈	(40) 30	32	-0.25",+0.5"
2	SWEEP 2/	19	21	23	25	27	29	10/
3	BACK LENGTH 3/	. 27	27 1/2	28	28 1/2	29	29 1/2	-0.5", +0.5"
4	SLEEVE LENGTH FROM CB 4/	33	33 3/4	34 1/2	35 1/4	36	36 3/4	-0.5", +0.5"
5	CUFF OPENING 5/	4	4 1/4	4 1/2	4 3/4	5	5 1/4	-0.25", +0.25"
6	CF ZIPPER LENGTH 6/	27 1/2	28	28 1/2	29	29 1/2	30	-0.5", +0.5"
7	COLLAR WIDTH AT CF 8/	3 3/4	3 3/4	3 3/4	3 3/4	3 3/4	3 3/4	-0.25", +0.25"
8	INSIDE PKT ELASTIC CUT LENGTH 8/	8 1/2	9 1/2	10 1/2	11 1/2	12 1/2	13 1/2	-0.25", +0.25"
9_	OUTSIDE PKT OPENING 9/	7	7	7	7	7	7	-0.25", +0.5"
SHORT		XS	S					
2	BACK LENGTH 3/	26	26 1/2		٨	20 1875		-0.5", +0.5"
4	SLEEVE LENGTH FROM CB 4/	31 1/2	32 1/4					-0.5", +0.5"
5	CF ZIPPER LENGTH 6/	26 1/2	27		W	Han I		-0.5", +0.5"
LONG			S	M	L	XL	2XL	
2	BACK LENGTH 3/		28 1/2	29 : .	29 1/2**	30.	30 1/2	-0.5", +0.5"
4	SLEEVE LENGTH FROM CB 4/	1000000	35 1/4	36	36 3/4*	37 1/2	38 1/4	
6	CF ZIPPER LENGTH 6/		29	29 1/2	30	30 1/2`	31	-0.5", +0.5"
XLONG				د		XL	2XL	
2	BACK LENGTH 3/			30.	30/2	31~' '	31 1/2	-0.5", +0.5"
4	SLEEVE LENGTH FROM CB 4/			37%	1 N.	39	39 3/4	-0.5", +0.5"
5	CF ZIPPER LENGTH 6/					31 1/2	32	-0.5", +0.5"
	1/ Across chest measurement is taken folded from edge to edge at the bottom of armhole							
	2/ Sweep measurement is taken from folded edge to folded edge, 2-1/2" above the top of the binding tape.							
	3/ Back Length Measurement is taken from bottom of center back neck straight to hem 4/ Sleeve length from CB is taken from bottom of center back neck straight to the bottom of sleeve binding with sleeve extended out flat taking care to pull the Taslan elbow patch flat and straighten out sleeve bottom binding. 5/ Cuff Opening is taken from edge to edge at sleeve hem 6/ CF zipper length should be measured by holding zipper tightly at top and bottom, then stretching zipper completely flat and, while holding taught, place against a calibrated steel ruler.							
	9/ Outside pocket opening measurement is taken from bartack to bartack							
	8/ For construction only							
	10/ XS: ±5/8"; S and M: ±3/4"; L and XL: +3/4", -1"; 2XL: +7/8", -1 3/8"							
	SEAM ALLOWANCE: 3/8": all seams except for - 1/4": neckline and 1/2": elbow patch							